Features

Professional Design

Designed X direction width set at 90cm instead of 60cm, effectively increase the printing speed of same resolution.

Anti-Collision System

Anti-collision system is equipped to protect the printhead and carriage all the time.

Auto Media Height Detecting

Automatic media height detecting function, provide great help for setting the proper print height.

Split Design (Base Rack Is Optional)

Printer and base rack using split design (base rack is optional), compact and easy to place, greatly reduce the package size, save the transportation fee.

High-Power Independent Vacuum System

Much more practical and functional than the vacuum system with small-power internal vacuum fans.

Specification

Model No.		FB-0906i Series	FB-0906D Series
Printhead		2/3 Pcs Epson Heads	2/3/4 Pcs Epson i1600-U1
Resolution		Max 1440 dpi	Max 2400 dpi
Media	Thickness	12 cm MAX	
	Size	900 x 600 mm	
	Types	Glass, Acrylic, Ceramic, Metal, Paper, Wood, Leather, PVC , PP, PE, PTFE Etc.	
Speed	Printing Mode	CMYK Mode	
	Draft	6 min for A1 full size	3 min for A1 full size
	Production	12 min for A1 full size	6 min for A1 full size
	Quality	18 min for A1 full size	9 min for A1 full size
Ink	Type	UV Ink	
	Color	CMYK / CMYK+W / CMYK+W+V / CMYK+W+V+Primer / CMYK+W+V+Fluorescent Color or Primer	
	Capacity	500 ml	
	Dry System	UV-LED Light System	
PC Operation System		Windows 7, Windows XP, Windows 10	
Environment		Temperature: 20-28°C, Humidity: 40%-60%	
Rip Software		Maintop / FlexiPRINT (Optional)	
Image Format		TIFF, JPEG, EPS, PDF...	
Power		AC 110/ 220V, 50/ 60Hz, 1800W	
Size	Machine	L2150×W1360×H900 mm	
	Packing	L2260×W1470×H1110 mm	
Weight	Machine	250 KG	
	Packing	350 KG	

Specifications are subject to change without notice.